



SKU:	RS-D21-PVC-8654
Chip Type:	NXP® MIFARE® DESFire® EV1 2K
Frequency:	HF 13.56 MHz
EEPROM:	2K bytes
Protocol:	ISO/IEC 14443-A, ISO/IEC 7816-4, NFC Forum Type 4
Compliance:	WEEE Directive
Industry:	Healthcare, retail, hospitality, events
Applications:	Access control, NFC, social engagement

RFID Card NXP® MIFARE® DESFire® EV1 2K

The RFID Card features the NXP® MIFARE® DESFire® EV1 2K chip, operating at 13.56 MHz with support for ISO/IEC 14443-A, ISO/IEC 7816-4, and NFC Forum Type 4 protocols. It offers 2K bytes of EEPROM for secure data storage.

Made from durable materials like PVC and eco-friendly options such as PET, ABS, and wood (WEEE Directive compliant), the card measures 85.6×54×0.88 mm and weighs about 5.8 grams. It supports various customizations including thermal printing, embossing, holograms, and UV printing for versatile use in access control and branding.

Physical Information	Material	Black core PVC, White core PVC, White core PET(WEEE Directive✓) White core ABS(WEEE Directive✓), Wooden(WEEE Directive✓)
	Size	85.6×54×0.88 mm(3.37"×2.125")
	Weight	About 5.8 g
	Surface Treatment	Glossy, matte or frosted
	Personalized Printing (NA for Wooden Cards)	Thermal transfer/dye sublimation
	Customization Options (NA for Wooden Cards)	Pre-Printing, Barcode Printing, Embossing, Holograms, Signature Panels, UV Printing, Hot Stamping, Punch Holes
	Operating Environment	0°C~+50°C, 20%~90% RH
	Storage Environment	+18°C~+28°C, 40%~60% RH
	Care Tips	1. Avoid excessive bending. 2. Keep away from water and collision. 3. Store in cool and dry place.
	Cleaning Tips	1. Use a soft, dry cloth. 2. Avoid harsh chemicals or abrasive cleaners. 3. Remove stains immediately.

Technical Information	Operating Frequency	13.56 MHz
	Protocol	ISO/IEC 14443-A, ISO/IEC 7816-4, NFC Forum Type 4
	Chip Type	NXP® MIFARE® DESFire® EV1 2K
	EEPROM	2K bytes
	Read Range	Up to 100 mm
	Security Features	Common Criteria Certification: EAL4+(Hardware and Software) Unique 7 bytes serial number for each device Optional "RANDOM" ID for enhance security and privacy Mutual three pass authentication Mutual authentication according to ISO/IEC 7816-4 1 card master key and up to 14 keys per application Hardware DES using 56/112/168 bit keys featuring key version, data authenticity by 8 byte CMAC Hardware AES using 128-bit keys featuring key version, data authenticity by 8 byte CMAC Data encryption on RF-channel Authentication on application level Hardware exception sensors Self-securing file system Backward compatibility to MF3ICD40: 4 byte MAC, CRC 16

Packaging Information	Packing Format	Single pieces, piece by piece
	Packing Method	Inner Packing: 200 pcs/case, G.W.: 1.26 kg Outer Packing: 5 cases/carton(1000 pcs) or 10 cases/carton(2000 pcs)
	Carton Dimension	1000 pcs: 23×20×17 cm 2000 pcs: 32.5×25×22.5 cm

● **Performance and Illustrations:** Graphs and visuals are for reference only; actual product performance may vary depending on usage and environment.
 ● **Storage and Handling Guidelines:** Follow standard ESD-safe storage and handling procedures to maintain product integrity and avoid damage.
 ● **Product Updates and Revisions:** rfidbridge.com may change products, specs, or services at any time without prior notice.
 ● **General Use Disclaimer:** Products are for general-purpose use and not intended for safety-critical or life-support applications.
 ● **Legal Notice:** Information is believed accurate but may change. rfidbridge.com is not liable for use-related issues or outcomes.