



NXP® NTAG® 213 NFC Card



SKU:	RS-N213-CR80
Chip Type:	NXP® NTAG® 213
Frequency:	HF 13.56 MHz
Protocol:	ISO/IEC 14443-A, NFC Forum Type 2
User Memory:	144 bytes
UID Memory:	7 bytes
EEPROM:	512 bytes
Read Range:	Up to 10 cm
Industry:	Hospitality, Events
Applications:	Brand Protection, Access Control, Event Ticketing

The NXP® NTAG® 213 NFC card fully complies with ISO/IEC 14443-A and NFC Forum Type 2 specifications. It features a 7-byte UID and provides 144 bytes of user memory organized into 36 pages. The card is produced in standard CR80 size, making it compatible with most direct thermal and thermal transfer card printers.

Physical Information	Material	Black Core PVC, White Core PVC, White Core PET (WEEE Directive✓), White Core ABS (WEEE Directive✓), Wooden (WEEE Directive✓)
	Card Size	86×54×0.88 mm
	Operating Environment	-20°C~+50°C, 20%~80% RH
	Storage Environment	+18°C~+28°C, 40%~60% RH
	Surface Treatment	Glossy, Matte or Frosted
	Personalized Printing (NA For Wooden Cards)	Thermal Transfer/Dye Sublimation
	Customization Options (NA For Wooden Cards)	Pre-Printing, Barcode Printing, Embossing, Holograms, Signature Panels, UV Printing, Hot Stamping, Punch Holes
	Care Tips	1. Avoid excessive bending 2. Keep away from water 3. Store in cool and dry place
Cleaning Tips		1. Use a soft, dry cloth 2. Avoid harsh chemicals or abrasive cleaners 3. Remove stains immediately

Technical Information	Operating Frequency	13.56 MHz
	Communication Protocol	ISO/IEC 14443-A, NFC Forum Type 2
	Chip Type	NXP® NTAG® 213
	UID Memory	7 bytes
	User Memory	144 bytes
	Security Features	32 bit password protection

Packaging Information	Packing Format	Single pieces, piece by piece
	Packing Quantity	200 pcs/case, G.W. : 1.3 kg
	Packing Method	1000 pcs or 2000 pcs/carton
	Carton Dimension	1000 pcs: 23×20×17 cm (G.W.: 7 KG); 2000 pcs: 48×23×14 cm (G.W.: 13 KG).

● **Performance and Illustrations:** Graphs and visuals are for reference only; actual product performance may vary depending on usage and environment.
 ● **Storage and Handling Guidelines:** Follow standard ESD-safe storage and handling procedures to maintain product integrity and avoid damage.
 ● **Product Updates and Revisions:** rfidbridge.com may change products, specs, or services at any time without prior notice.
 ● **General Use Disclaimer:** Products are for general-purpose use and not intended for safety-critical or life-support applications.
 ● **Legal Notice:** Information is believed accurate but may change. rfidbridge.com is not liable for use-related issues or outcomes.