



ABS-01



ABS-02



ABS-03



ABS-06



ABS-08



ABS-08(w/o slot)

NXP® MIFARE Classic® EV1 4K HF ABS RFID Key-Fob



SKU:	RS-S70-ABS
Chip Type:	NXP® MIFARE Classic® EV1 4K
Frequency:	HF 13.56 MHz
EEPROM Memory:	4096 bytes
Protocol:	ISO/IEC 14443-A, NFC Forum Type 2
Compliance:	WEEE Directive
Industry:	Hospitality, Educational Institutions, Transportation, Industrial, Hospitals, Government, Events
Applications:	Access Control, Attendance Tracking, Activity Tracking, Loyalty Programs, Event ticketing, Car parking

The NXP® MIFARE Classic® EV1 4K HF ABS RFID Key-Fob features a robust ABS key fob housing a high-capacity 4K memory chip. Designed for durability, this key fob is ideal for everyday use and fits conveniently on keychains.







This versatile HF KEY FOB Tag with NXP MIFARE Classic® 4K technology is well-suited for applications such as transportation ticketing, secure NFC access control, membership management, and hotel guest identification, providing reliable performance in all these scenarios.

Physical Information	Material	ABS
	Compliance	WEEE Directive
	Characteristics	Waterproof
	Operating Environment	-20°C~+80°C
	Storage Environment	+18°C~+28°C

Technical Information	Operating Frequency	13.56 MHz
	Protocol	ISO/IEC 14443-A, NFC Forum Type 2
	Chip Type	NXP® MIFARE Classic® EV1 4K
	EEPROM Memory	4096 bytes
	Read Range	2-10 cm
	Security Features	Manufacturer programmed 7-byte UID or 4-byte NUID identifier for each device Random ID support Mutual three pass authentication (ISO/IEC DIS 9798-2) Individual set of two keys per sector to support multi-application with key hierarchy

Packaging Information	Packing Format	Packed in carton
	Carton Dimension	49×24×20 cm

Specification	ABS-01	ABS-02	ABS-03	ABS-06	ABS-08	ABS-08(w/o slot)
Size	44×31×5 mm	35×28×4.8 mm	40×32×3.8 mm	51×32×5.9 mm	37×30×8 mm	37×30×8 mm
Color	Red Yellow Blue Black Grey Green Orange	Red Yellow Blue Black Grey Green Orange	Red Yellow Blue Black White Grey Green Orange Brown Light Green	Red Yellow Blue	Red Yellow Blue Black Grey Green Orange Light Green	Red Yellow Blue Black Grey Green Orange Light Green
Weight	5 g	4 g	4 g	5.5 g	5 g	5 g
Quantity	50 pieces/bag, 1500 pieces/carton	100 pieces/bag, 2500 pieces/carton	100 pieces/bag, 2500 pieces/carton	50 pieces/bag, 1500 pieces/carton	50 pieces/bag, 2000 pieces/carton	50 pieces/bag, 2000 pieces/carton
Weight	N.W. 7.5 kg/carton, G.W. 8.5 kg/carton	N.W. 10 kg/carton, G.W. 11 kg/carton	N.W. 10 kg/carton, G.W. 11 kg/carton	N.W. 8.25 kg/carton, G.W. 9 kg/carton	N.W. 10 kg/carton, G.W. 11 kg/carton	N.W. 10 kg/carton, G.W. 11 kg/carton



● **Performance and Illustrations:** Graphs and visuals are for reference only; actual product performance may vary depending on usage and environment.
 ● **Storage and Handling Guidelines:** Follow standard ESD-safe storage and handling procedures to maintain product integrity and avoid damage.
 ● **Product Updates and Revisions:** [rfidbridge.com](https://www.rfidbridge.com) may change products, specs, or services at any time without prior notice.
 ● **General Use Disclaimer:** Products are for general-purpose use and not intended for safety-critical or life-support applications.
 ● **Legal Notice:** Information is believed accurate but may change [rfidbridge.com](https://www.rfidbridge.com) is not liable for use-related issues or outcomes.