



NXP ICODE®SLIX HF RFID PET Tag with Adhesive



SKU:	RS-SLIX-PET3M-3020
Chip Type:	NXP ICODE®SLIX
Frequency:	HF 13.56 MHz
Protocol:	ISO/IEC 15693, ISO/IEC 18000-3, NFC Forum Type 5
EEPROM:	1024 bits
User Memory:	896 bits
Compliance:	WEEE Directive
Industry:	Logistics, Retail, Healthcare
Applications:	Asset Tracking, Document Management, Inventory, NFC

The NXP ICODE®SLIX HF RFID PET Tag with Adhesive is a high-frequency (13.56 MHz) smart tag featuring 1024 bits of EEPROM (896 bits user memory). This plain white card is crafted with a matte finish and laminated overlay, providing a smooth, durable surface ideal for printing and customization. It complies with ISO/IEC 15693, ISO/IEC 18000-3, NFC Forum Type 5 standards, ensuring fast data access and reliable NFC compatibility.

Made of PET with 3M adhesive, this compact tag (30 × 20 × 0.73 mm) is easy to apply on paper cartons, plastic, and wood. Perfect for smart packaging, asset tracking, and inventory management.

Physical Information	Material	PET & 3M adhesive
	Size	30 × 20 × 0.73 mm
	Specification	White card Matte finish Laminated overlay
	Compliance	WEEE Directive
	Storage Environment	+18°C~+28°C, 20%~90% RH
	Mounting Method	Stick
	Surface	Paper carton, Plastic, Wood

Technical Information	Operating Frequency	13.56 MHz
	Protocol	ISO/IEC 15693, ISO/IEC 18000-3, NFC Forum Type 5
	Chip Type	NXP ICODE®SLIX
	EEPROM	1024 bits
	User Memory	896 bits
	UID	64 bits
	Read Range	Up to 1.5 m
	Security Features	Unique identifier for each device Lock mechanism for each user memory block (write protection) Lock mechanism for DSFID, AFI, EAS Password (32-bit) protected EAS and AFI functionality

Dimensions
(Unit: mm)



● **Performance and Illustrations:** Graphs and visuals are for reference only; actual product performance may vary depending on usage and environment. ● **Storage and Handling Guidelines:** Follow standard ESD-safe storage and handling procedures to maintain product integrity and avoid damage. ● **Product Updates and Revisions:** rfidbridge.com may change products, specs, or services at any time without prior notice. ● **General Use Disclaimer:** Products are for general-purpose use and not intended for safety-critical or life-support applications. ● **Legal Notice:** Information is believed accurate but may change. rfidbridge.com is not liable for use-related issues or outcomes.