



SKU:	RS-SLX2-CP3M-D40
Chip Type:	NXP® ICODE® SLIX2
Frequency:	HF 13.56 MHz
TID Memory:	64 bytes
User Memory:	320 bytes
Protocol:	ISO/IEC 15693, ISO/IEC 18000-3M1, NFC Forum Type 5
Read Range:	Up to 1.5 m
Certificate:	WEEE compliant
Industry:	Retail, Events
Applications:	Document Management, Library, Social Engagement, NFC, Warehouse



NXP® ICODE® SLIX2 NFC Label


Enhance your tracking accuracy with our ISO/IEC 15693 NFC label, featuring a compact Ø40mm design and powered by the advanced NXP® ICODE® SLIX2 chip. This label offers extended reading distances, ensuring reliable performance in various applications.

Specifically designed for library use, the ICODE® SLIX2 chip provides exceptional data storage capabilities, making it an ideal solution for efficient asset management and inventory tracking in library environments.

Physical Information	Material	Coated Paper & 3M adhesive
	Label Size	Ø40 mm
	Antenna Size	Ø34 mm
	Operating Environment	-20°C~+50°C, 20%~80% RH
	Storage Environment	+18°C~+28°C, 40%~60% RH
	Mounting Method	Stick
	Certificate	WEEE compliant
	Surface	Plastic, Paper Carton, Wood
	Handling Precautions	1. Do not bend. 2. Keep away from water and collision. 3. Labels with black-dot marks are bad ones, do not use.

Technical Information	Operating Frequency	13.56 MHz
	Communication Protocol	ISO/IEC 15693, ISO/IEC 18000-3M1, NFC Forum Type 5
	Read Range	Up to 1.5 m
	Chip Type	NXP® ICODE® SLIX2
	User Memory	320 bytes
	UID Memory	64 bytes
	Security Features	32-bit protected EAS and AFI functionality

Packing Information	Packing Format	Packed in roll, vacuumed packing in ESD bag
	Roll OD	Max. 180 mm
	Core ID	3 inch(76.2 ± 0.50 mm)
	Packing Quantity	1000 pcs/roll, per roll 1.5 kg



● **Performance and Illustrations:** Graphs and visuals are for reference only; actual product performance may vary depending on usage and environment.
 ● **Storage and Handling Guidelines:** Follow standard ESD-safe storage and handling procedures to maintain product integrity and avoid damage.
 ● **Product Updates and Revisions:** rfidbridge.com may change products, specs, or services at any time without prior notice.
 ● **General Use Disclaimer:** Products are for general-purpose use and not intended for safety-critical or life-support applications.
 ● **Legal Notice:** Information is believed accurate but may change. rfidbridge.com is not liable for use-related issues or outcomes.