



NXP® MIFARE Plus® S 4K RFID Card



SKU:	RS-MFPS4k-CR80
Chip Type:	NXP® MIFARE Plus® S 4K
Frequency:	HF 13.56 MHz
EEPROM:	500 bytes
UID:	4 bytes / 7 bytes
Protocol:	ISO/IEC 14443-A
Industry:	Events, Healthcare, Transportation, Business
Applications:	Access Control, NFC, ETC Toll Payment, Vehicle Tracking

The NXP® MIFARE Plus® S 4K CR80 RFID Card combines robust data security with exceptional performance, making it the perfect solution for modern access control and smart card systems. Operating at 13.56 MHz and compliant with ISO/IEC 14443-A, this card provides 4 kB EEPROM, ensuring ample capacity for multi-application environments such as transportation, corporate identification, campus systems, and cashless payment solutions. Its AES-128 encryption ensures advanced data protection and secure authentication in every tap.

Engineered for smooth integration, the MIFARE Plus® S 4K card offers an easy upgrade path from MIFARE Classic systems to enhanced AES-level security — without requiring major infrastructure changes. Its fast data transmission, wide reader compatibility, and durable CR80 PVC construction guarantee reliable long-term performance. Designed for organizations seeking scalability, security, and convenience, this RFID card is a smart investment for building the next generation of secure and efficient contactless ecosystems.

Physical Information	Material	Black core PVC, White core PVC, White core PET(WEEE Directive✓), White core ABS(WEEE Directive✓), Wooden(WEEE Directive✓)
	Card Size	85.6×54×0.88 mm
	Net Weight	About 5.8 g
	Operating Environment	-20°C~+50°C, 20%~80% RH
	Storage Environment	+18°C~+28°C, 40%~60% RH
	Surface Treatment	Glossy, Matte or Frosted
	Personalized Printing (NA for Wooden Cards)	Thermal Transfer/Dye Sublimation
	Customization Options (NA for Wooden Cards)	Pre-Printing, Barcode Printing, Embossing, Holograms, Signature Panels, UV Printing, Hot Stamping, Punch Holes
	Care Tips	1. Avoid excessive bending 2. Keep away from water 3. Store in cool and dry place
Technical Information	Cleaning Tips	1. Use a soft, dry cloth 2. Avoid harsh chemicals or abrasive cleaners 3. Remove stains immediately

Technical Information	Operating Frequency	13.56 MHz
	Communication Protocol	ISO/IEC 14443-A
	Chip Type	NXP® MIFARE Plus® S 4K
	Data Transfer	848 kbit/s
	EEPROM	500 bytes
	UID	4 bytes / 7 bytes
	NUID	4 bytes
	Virtual Card Concept	Support
	Anti-Tearing Mechanism	Writing AES keys
	Keys Can Be Stored As	MIFARE CRYPTO1 keys (2 × 48-bit per sector) and as AES keys (2 × 128-bit per sector)
	Simple Fixed Memory Structure Compatible With	MIFARE Classic 1K and MIFARE Classic 4K (sectors, blocks)
	Proximity Check	Support
	Common Criteria Certification	EAL4+
	Security Features	AES-128 Encryption for authenticity and integrity

Packaging Information	Packing Format	Single pieces, piece by piece
	Packing Quantity	200 pcs/case, G.W. : 1.26 kg
	Packing Method	1000 pcs or 2000 pcs/carton
	Carton Dimension	1000 pcs: 23x20x17cm (G.W.: 6.3 KG); 2000 pcs: 48x23x14cm (G.W.: 12.6 KG).

● **Performance and Illustrations:** Graphs and visuals are for reference only; actual product performance may vary depending on usage and environment.
 ● **Storage and Handling Guidelines:** Follow standard ESD-safe storage and handling procedures to maintain product integrity and avoid damage.
 ● **Product Updates and Revisions:** [rfidbridge.com](https://www.rfidbridge.com) may change products, specs, or services at any time without prior notice.
 ● **General Use Disclaimer:** Products are for general-purpose use and not intended for safety-critical or life-support applications.
 ● **Legal Notice:** Information is believed accurate but may change. [rfidbridge.com](https://www.rfidbridge.com) is not liable for use-related issues or outcomes.