



Avery Dennison® NXP® UCODE® 9 ARC Certified Coated paper RFID UHF Label

SKU:	AD-387-U9
Chip Type:	NXP® UCODE® 9
Frequency:	UHF 860-960 MHz
EPC Memory:	96 bits
Protocol:	ISO/IEC 18000-63, EPCglobal Gen2v2.1
Read Range:	Up to 18m (ETSI standard) Up to 16m (FCC standard)
Industry:	Retail, Apparel and Fashion, Jewelry, Logistics
Applications:	Asset Tracking, Electronics, Jeweleries & Sunglasses, Gaming and Toys, Inventory, Warehouse




This ARC-certified RFID label enables retailers to efficiently capture clothing item data and combat brand counterfeiting. Embedded with a high-performance RFID chip, the label can be read by RFID readers and transmit encoded data to backend systems for real-time tracking, analysis, and storage. It complies with EPCglobal Gen 2v2.1 and ISO/IEC 18000-63 standards, ensuring global interoperability.


Specifically designed for apparel, retail, and logistics, this label is widely applied in supply chain management, inventory control, furniture tracking, and brand protection. Most importantly, its ARC certification qualifies products for compliance with Walmart's RFID mandate, facilitating smoother entry into major retail channels.

Reading performance

Reading range under different frequency



Orientation Sensitivity



Physical Information


Material	Coated Paper
Size	54×34 mm
Operating Environment	-20°C~+50°C, 20%~80% RH
Storage Environment	+18°C~+28°C, 40%~60% RH
Mounting Method	Paper Carton, Plastic, Wood
Surface	Stick
ARC Specs	F, I, L, Q, R, W5, W6, Y2
Handling Precautions	1. Do not bend. 2. Keep away from water and collision. 3. Labels with black-dot marks are bad ones, do not use.

Technical Information

Operating Frequency	UHF 860~960 MHz
Communication Protocol	ISO/IEC 18000-63, EPCglobal Gen2v2.1
Read Range	Up to 18m (ETSI standard) Up to 16m (FCC standard)
Chip Type	NXP® UCODE® 9
EPC Memory	96 bits
Security Features	32 bits kill password

Packing Information	Packing Format	Packed in roll, vacuummed packing in ESD bag.
	Roll OD	Max. 140 mm
	Core ID	3 inch/76.2 ± 0.50mm
	Packing Quantity	1000 Pcs/roll, per roll 1 kg

Label Dimensions
(Unit: mm)



● **Performance and Illustrations:** Graphs and visuals are for reference only; actual product performance may vary depending on usage and environment.
 ● **Storage and Handling Guidelines:** Follow standard ESD-safe storage and handling procedures to maintain product integrity and avoid damage.
 ● **Product Updates and Revisions:** rfidbridge.com may change products, specs, or services at any time without prior notice.
 ● **General Use Disclaimer:** Products are for general-purpose use and not intended for safety-critical or life-support applications.
 ● **Legal Notice:** Information is believed accurate but may change rfidbridge.com s not liable for use-related issues or outcomes.