

Fixed Android RFID Reader

AZF-M1



Key Features

Operating Frequency
UHF 860-960 MHz

Engine
Based on Impinj E710/Impinj Indy R2000

International Standard
EPC Class 1 Gen 2, ISO/IEC 18000-6C

CPU
Quad-core, 2.0GHz

RAM+ROM
3 GB+32 GB

Operating System
Android 11

Ethernet Interface
10/100 Base-T Ethernet (RJ45)

WLAN
IEEE802.11 b/g/n, 2.4G

Bluetooth
Bluetooth 4.0

1. Product Overview

This is a newly launched high-performance fixed RFID reader. Adopting Android 11 operating system, 2.0GHz quadcore CPU, This possesses powerful data processing capabilities. Based on the Impinj E710/ R2000 chip, the reader has stronger UHF performance. The reader Integrates RS232, RJ45, HDMI and other interfaces, and supports DC, POE, POE+ power supplies. It can meet the application needs in complex environments such as warehousing, file management, library management, production line management, medical device cabinet, unmanned retail, etc.

2. Product Parameters

2.1 Physical Characteristics

SKU	AZF-M1
Dimensions	247×151×35 mm/9.72×5.94×1.38 in
Weight	1000 g/35.27 oz. (Host Only)
Material	Aluminium alloy
Input Voltage	DC 10V – 24V
Standby Current	<140 mA
Work Current	600 mA +/-5% @ DC 24V Input
Comm Interface	1×RS-232 , 1×RJ45, 1×USB Host, 1×USB Device
Display Interface	HDMI Type A, support 720P HD video output
GPIO	4×input optocouplers, 4×output optocouplers, with isolation, 1×Wiegand
Baud Rate	115200bps
Cooling Mode	Air cooling
Power	DC(24 V), POE(802.3af 13 W), POE+(802.3at 25.5 W)

2.2 Performance

CPU	Quad-core, 2.0GHz
RAM+ROM	3 GB+32 GB

2.3 Developing Environment

Operating System	Android 11
SDK	Support Software Development Kit
Language	Java
Tool	Eclipse/Android Studio

2.4 Communication

Ethernet Interface	10/100 Base-T Ethernet (RJ45)
WLAN	IEEE802.11 b/g/n, 2.4G
Bluetooth	Bluetooth 4.0

2.5 User Environment

Operating Temp.	-25℃~+65℃ (-13°F~+149°F)
Storage Temp.	-40℃~+85℃ (40°F~+185°F)
Humidity	10%~95%

2.6 RFID UHF

Engine	Based on Impinj E710/Impinj Indy R2000
Protocol	EPC Class 1 Gen 2, ISO/IEC 18000-6C
Frequency	865-868 MHz, 920-925 MHz, 902-928 MHz
Output Power	1W(30 dBm, support +5~+30 dBm adjustable, POE/DC power) 2W Optional(33 dBm, support +10~+33 dBm adjustable, POE+/DC power, for Latin America, etc.)
Output Power Precision	+/- 1 dB
Output Power Flatness	+/- 0.2 dB
Receive Sensitivity	<-84 dBm
Fastest Read Rate	950+ tags/sec
RSSI	Supported
Ambient Temp Monitor	Supported
Antenna Detector	Supported
Antenna	Supporting a variety of antennas, such as 6dBic, 9dBic, etc
Antenna Port	4×Channel 50Ω RF Connector RP-TNC Female