



NXP® UCODE® 8M UHF RFID Card



SKU:	RS-U8M-CR80
Chip Type:	NXP® UCODE® 8M
Frequency:	UHF 860-960 MHz
Protocol:	EPCglobal Gen2v2
EPC Memory:	96 bits
User Memory:	32 bits
UID Memory:	96 bits of Serialized TID with 48 bit serial number
Industry:	Logistics, Healthcare
Applications:	Baggage Tagging, Brand Protection, Inventory, Supply Chain Management

Blank or customized printing RFID cards are available in various dimensions to meet different application needs.

NXP® UCODE® 8M is optimized for item serialization in retail management, supply chain management, shipping services, and other related applications.

Physical Information	Material	Black Core PVC, White Core PVC, White Core PET (WEEE Directive✓), White Core ABS (WEEE Directive✓), Wooden (WEEE Directive✓)
	Card Size	85.6×54×0.88 mm
	Operating Environment	-20°C~+50°C, 20%~80% RH
	Storage Environment	+18°C~+28°C, 40%~60% RH
	Surface Treatment	Glossy, Matte or Frosted
	Personalized Printing (NA For Wooden Cards)	Thermal Transfer/Dye Sublimation
	Customization Options (NA For Wooden Cards)	Pre-Printing, Barcode Printing, Embossing, Holograms, Signature Panels, UV Printing, Hot Stamping, Punch Holes
	Care Tips	1. Avoid excessive bending 2. Keep away from water 3. Store in cool and dry place
	Cleaning Tips	1. Use a soft, dry cloth 2. Avoid harsh chemicals or abrasive cleaners 3. Remove stains immediately
Technical Information	Operating Frequency	860-960 MHz
	Communication Protocol	EPCglobal Gen2v2
	Chip Type	NXP® UCODE® 8M
	Operating Mode	Passive
	UID Memory	96 bits of Serialized TID with 48 bit serial number
	User Memory	32 bits
	EPC Memory	96 bits
	Security Features	Access password: 32 bits
Packaging Information	Packing Format	Single pieces, piece by piece
	Packing Quantity	200 pcs/case, G.W. : 1.3 kg
	Packing Method	1000 pcs or 2000 pcs/carton
	Carton Dimension	1000 pcs: 23×20×17 cm (G.W.: 7 KG); 2000 pcs: 48×23×14 cm (G.W.: 13 KG).

● **Performance and Illustrations:** Graphs and visuals are for reference only; actual product performance may vary depending on usage and environment.
 ● **Storage and Handling Guidelines:** Follow standard ESD-safe storage and handling procedures to maintain product integrity and avoid damage.
 ● **Product Updates and Revisions:** [rfidbridge.com](https://www.rfidbridge.com) may change products, specs, or services at any time without prior notice.
 ● **General Use Disclaimer:** Products are for general-purpose use and not intended for safety-critical or life-support applications.
 ● **Legal Notice:** Information is believed accurate but may change. [rfidbridge.com](https://www.rfidbridge.com) is not liable for use-related issues or outcomes.