



NXP® NTAG®424 DNA Label

SKU: RS-424-UCP-D30

Chip Type: NXP® NTAG®424 DNA

Frequency Band: HF 13.56 MHz

Protocol: ISO/IEC 14443-A,
ISO/IEC 7816-4,
NFC Forum Type 4

User Memory: 416 bytes

UID Memory: 7 bytes

Read Range: Up to 10 cm

Industry: Retail, Jewelry, Apparel and Fashion, Collection

Applications: Brand Protection, Jewelries & Sunglasses,
NFC, Product Authentication, Document
Management, Social Engagement




The NXP® NTAG® 424 DNA Coated Paper NFC Label delivers advanced product authentication and consumer engagement in a sleek, printable format. Powered by AES-128 encryption and SUN authentication, it ensures maximum protection against counterfeiting.

With its premium coated paper surface, this label is perfect for smart packaging, retail, wine & spirits, and pharmaceuticals, enabling brands to secure products, build trust, and unlock exclusive digital experiences with a single tap.

Physical Information	Material	FSC-Certified Coated Paper
	Label Size	Ø30 mm
	Antenna Size	Ø27 mm
	Operating Environment	-20°C~+50°C, 20%~80% RH
	Storage Environment	+18°C~+28°C, 40%~60% RH
	Mounting Method	Stick
	Surface	Paper carton, Plastic, Wood
	Handling Precautions	1. Do not bend. 2. Keep away from water and collision. 3. Labels with black-dot marks are bad ones, do not use.

Technical Information	Operating Frequency	13.56 MHz
	Protocol	ISO/IEC 14443-A, ISO/IEC 7816-4, NFC Forum Type 4
	Chip Type	NXP® NTAG®424 DNA
	Read Range	Up to 10 cm
	User Memory	416 bytes
	UID Memory	7 bytes
	Security Features	Standard AES-128 cryptography or LRP wrapped AES operation
	Advanced Data Protection	SUN message authentication
	Anti-collision	Support

Packaging Information	Packing Format	Packed in roll, vacuumed packing in ESD bag
	Roll OD	Max.205 mm
	Core ID	3 inch(76.2 ± 0.50 mm)
	Packing Quantity	1000 Pcs/roll, per roll 0.325 kg



● **Performance and Illustrations:** Graphs and visuals are for reference only; actual product performance may vary depending on usage and environment.
 ● **Storage and Handling Guidelines:** Follow standard ESD-safe storage and handling procedures to maintain product integrity and avoid damage.
 ● **Product Updates and Revisions:** rfidbridge.com may change products, specs, or services at any time without prior notice.
 ● **General Use Disclaimer:** Products are for general-purpose use and not intended for safety-critical or life-support applications.
 ● **Legal Notice:** Information is believed accurate but may change rfidbridge.com s not liable for use-related issues or outcomes.