



SKU:	RS-SLIXS-CR80
Chip Type:	NXP® ICODE® SLIX-S
Frequency:	HF 13.56 MHz
Protocol:	ISO/IEC 15693, ISO/IEC 18000-3, NFC Forum Type 5
Read Range:	Up to 1.5 m
EEPROM:	256 bytes
UID Memory:	8 bytes
Industry:	Hospitality, Events, Apparel and Fashion, Library
Applications:	Libraries, Smart Fitting Room, Vicinity Card ETC, Item Level Tagging in Pharmaceutical Supply Chains, Counterfeit Protection for Consumer Goods.

NXP® ICODE® SLIX-S NFC Card

Blank or customized printing NFC cards are available in a variety of dimensions to meet different application needs. These cards can be tailored with specific designs, logos, or layouts for branding or identification purposes.

The NXP® ICODE® SLIX-S IC is ideal for NFC smart card applications that require larger memory capacity and a higher level of security. It is also compliant with ISO/IEC 15693, ISO/IEC 18000-3, NFC Forum Type 5, ensuring reliable performance and compatibility with NFC-enabled devices.

Physical Information	Material	Black Core PVC, White Core PVC, White Core PET (WEEE Directive✓), White Core ABS (WEEE Directive✓), Wooden (WEEE Directive✓)
	Card Size	86×54×0.88 mm
	Operating Environment	-20°C~+50°C, 20%~80% RH
	Storage Environment	+18°C~+28°C, 40%~60% RH
	Surface Treatment	Glossy, Matte or Frosted
	Personalized Printing (NA For Wooden Cards)	Thermal Transfer/Dye Sublimation
	Customization Options (NA For Wooden Cards)	Pre-Printing, Barcode Printing, Embossing, Holograms, Signature Panels, UV Printing, Hot Stamping, Punch Holes
	Care Tips	1. Avoid excessive bending 2. Keep away from water 3. Store in cool and dry place
Cleaning Tips		1. Use a soft, dry cloth 2. Avoid harsh chemicals or abrasive cleaners 3. Remove stains immediately

Technical Information	Operating Frequency	13.56 MHz
	Communication Protocol	ISO/IEC 15693, ISO/IEC 18000-3, NFC Forum Type 5
	Chip Type	NXP® ICODE® SLIX-S
	Read Range	Up to 1.5 m
	UID Memory	8 bytes
	User Memory	160 bytes
	Security Features	Privacy password: 32 bits, Destroy password: 32 bits

Packaging Information	Packing Format	Single pieces, piece by piece
	Packing Quantity	200 pcs/case, G.W. : 1.3 kg
	Packing Method	1000 pcs or 2000 pcs/carton
	Carton Dimension	1000 pcs: 23×20×17 cm (G.W.: 7 KG); 2000 pcs: 48×23×14 cm (G.W.: 13 KG).

● **Performance and Illustrations:** Graphs and visuals are for reference only; actual product performance may vary depending on usage and environment.
 ● **Storage and Handling Guidelines:** Follow standard ESD-safe storage and handling procedures to maintain product integrity and avoid damage.
 ● **Product Updates and Revisions:** rfidbridge.com may change products, specs, or services at any time without prior notice.
 ● **General Use Disclaimer:** Products are for general-purpose use and not intended for safety-critical or life-support applications.
 ● **Legal Notice:** Information is believed accurate but may change rfidbridge.com's not liable for use-related issues or outcomes.