




NXP® ICODE® SLIX2 NFC Label

SKU:	RS-SLX2-CP-5030
Chip Type:	NXP® ICODE® SLIX2
Frequency:	HF 13.56 MHz
TID Memory:	64 bytes
User Memory:	320 bytes
Protocol:	ISO/IEC 15693, ISO/IEC 18000-3M1, NFC Forum Type 5
Read Range:	Up to 1.5 m
Certificate:	WEEE compliant
Industry:	Retail, Events
Applications:	Document Management, Library, Social Engagement, NFC, Warehouse




Experience exceptional tracking and data management with our ISO/IEC 15693 and NFC Forum Type 5 50×30mm NFC label, powered by the advanced NXP® ICODE® SLIX2 chip. Designed for robust data storage and superior reading distances, this label ensures seamless integration into your RFID applications.

Perfect for inventory management, asset tracking, and access control, this label offers precision and reliability to optimize your operations. Elevate your business with cutting-edge technology that sets a new standard in performance and efficiency.

Physical Information	Material	Coated Paper
	Label Size	50×30 mm
	Antenna Size	37×22 mm
	Operating Environment	-20°C~+50°C, 20%~80% RH
	Storage Environment	+18°C~+28°C, 40%~60% RH
	Mounting Method	Stick
	Certificate	WEEE compliant
	Surface	Plastic, Paper Carton, Wood
	Handling Precautions	1. Do not bend. 2. Keep away from water and collision. 3. Labels with black-dot marks are bad ones, do not use.

Technical Information	Operating Frequency	13.56 MHz
	Communication Protocol	ISO/IEC 15693, ISO/IEC 18000-3M1, NFC Forum Type 5
	Read Range	Up to 1.5 m
	Chip Type	NXP® ICODE® SLIX2
	User Memory	320 bytes
	UID Memory	64 bytes
	Security Features	32-bit protected EAS and AFI functionality

Packing Information	Packing Format	Packed in roll, vacuummed packing in ESD bag
	Roll OD	Max. 185 mm
	Core ID	3 inch(76.2 ± 0.50 mm)
	Packing Quantity	1000 pcs/roll, per roll 0.5 kg



● **Performance and Illustrations:** Graphs and visuals are for reference only; actual product performance may vary depending on usage and environment.
 ● **Storage and Handling Guidelines:** Follow standard ESD-safe storage and handling procedures to maintain product integrity and avoid damage.
 ● **Product Updates and Revisions:** rfidbridge.com may change products, specs, or services at any time without prior notice.
 ● **General Use Disclaimer:** Products are for general-purpose use and not intended for safety-critical or life-support applications.
 ● **Legal Notice:** Information is believed accurate but may change. rfidbridge.com is not liable for use-related issues or outcomes.